

Webservice - getAlertDetailsResponse

Request

Response

Response

The request getAlertDetailsResponse must have the following structure :

| Element | Description | Required | Format | Condition |
|-----------------------|--|----------|--|---------------------|
| result | Result information. To be valued at the value "3" | Yes | Object result | Required since 2011 |
| AlertId | Alert identifier | Yes | AN20 | |
| ExplanationCode | LCLF rule code | No | AN20 | |
| ExplanationLabel | LCLF rule name | No | AN100 | |
| TransactionStatus | Status of the transaction | Yes | AN50 | |
| MerchantLabel | Merchant name | Yes | AN100 | |
| PosLabel | Point of sale Name | Yes | AN50 | |
| TransactionId | Identifier of the LCLF transaction | Yes | AN20 | |
| SecurityLevel | Security level of the transaction composed of two fields: "field1, field2" corresponding to two infos: use of cvv, use of 3dsecure Example : with cvv, without 3dSecure | Yes | AN50 | |
| TransactionDate | Transaction date. Format : dd/MM/yy HH:mm | Yes | AN14 | |
| TransactionAmount | Transaction amount | Yes | AN | |
| TransactionCurrency | Transaction currency | Yes | AN | |
| PaymentType | Type of the payment method of the transaction | Yes | AN20 | |
| PaymentData | Cardholder's data. transaction.masked_card_number or transactionPaypal.external_payer_email or transactionMoneybooker.buyer_email | Yes | AN | |
| HolderName | Cardholder's name | No | AN | |
| ReferenceData | Transaction reference | Yes | AN50 | |
| CustomerId | Consumer Id | No | AN50 | |
| BuyerFirstName | Consumer first name | No | AN100 | |
| BuyerLastName | Consumer last name | No | AN100 | |
| CustomerTransHist | Information on transaction history of the payment method | Yes | Object CustomerTransHist | |
| PaymentMeansTransHist | Information on transaction history of the payment method | Yes | Object PaymentMeansTransHist | |
| AlertsTransHist | Alert history information | Yes | Object AlertsTransHist | |