

Webservice - getAlertDetailsResponse

Request	Response
---------	----------

Response

The request getAlertDetailsResponse must have the following structure :

Element	Description	Required	Format	Condition
result	Result information. To be valued at the value "3".	Yes	Object result	Required since 2011
AlertId	Alert identifier.	Yes	AN20	
ExplanationCode	LCLF rule code.	No	AN20	
ExplanationLabel	LCLF rule name.	No	AN100	
TransactionStatus	Status of the transaction.	Yes	AN50	
MerchantLabel	Merchant name.	Yes	AN100	
PosLabel	Point of sale Name.	Yes	AN50	
TransactionId	Identifier of the LCLF transaction.	Yes	AN20	
SecurityLevel	Security level of the transaction composed of two fields: "field1, field2" corresponding to two infos: use of cvv, use of 3dsecure. Example : with cvv, without 3dSecure.	Yes	AN50	
TransactionDate	Transaction date. Format : dd/MM/yy HH:mm.	Yes	AN14	
TransactionAmount	Transaction amount.	Yes	AN	
TransactionCurrency	Transaction currency.	Yes	AN	
PaymentType	Type of the payment method of the transaction.	Yes	AN20	
PaymentData	Cardholder's data. transaction.masked_card_number or transactionPaypal. external_payer_email or transactionMoneybooker.buyer_email.	Yes	AN	
HolderName	Cardholder's name.	No	AN	
ReferenceData	Transaction reference.	Yes	AN50	
CustomerId	Consumer Id.	No	AN50	
BuyerFirstName	Consumer first name.	No	AN100	
BuyerLastName	Consumer last name.	No	AN100	
CustomerTransHist	Information on transaction history of the payment method.	Yes	Object CustomerTransHist	
PaymentMeansTransHist	Information on transaction history of the payment method.	Yes	Object PaymentMeansTransHist	
AlertsTransHist	Alert history information.	Yes	Object AlertsTransHist	